

Variofix Classic bathroom drain DN 50, vert., Slotted grating, K 3



Article information

Item no.: 40250.50 GTIN: 4026092028599 Price group: 10

Advantages

- Odour trap height: 50 mm
- Lip seal fixed on the drain body
- Side adjustable cover

Description

The Classic bathroom drain is suitable for indoor floor drainage. The drain made of ABS is equipped with a telescopic, height-adjustable upper section made of polymer, a removable odour trap as well as a secure, reliably installed seal. Including upper section for combined waterproofing for alternative WP layer.

Variant Waterproofing layer on the upper section: Water supply: Sealing water height: Discharge rate (l/s) with 20 mm backwater:	Enclosed sealing collar to be glued (bd) according to DIN 18534 W3-I 50 mm 0,8
General characteristics Standard: Nominal size (DN): Outer diameter (OD):	EN 1253-1 50 50 mm
Dimensions Vertical adjustment: Net weight: Gross weight: Cutout dimension, width: Cutout dimension, length: Vertical adjustment: Length: Width: Packaging dimension: Packaging dimension: Packaging dimension:	45 - 110 mm 1,28 kg 1,51 kg 180 mm 220 mm vertically adjustable upper section 312 mm 312 mm length width height

Tank/drain body



Number of outlets: Material of drain body: System:

Coverage features Type of cover: Cover material: Colour of cover: Width of cover: Length of cover: Surface: Frame material: Cover locking: Load class: Rim length: Rim material: Shape of upper section: Upper section material: Odour trap: 1 ABS vertical

Slotted cover Stainless steel 14301 silver 95 mm 95 mm Polished SST ABS placed K 3 (EN 1253-1) 132 mm 132 mm square ABS included