

Chamber module LW 1000 floor slab Access LW 600, 2130-2379 mm, Class D



Article information

Item no.: 8740043 GTIN: 4026092065587

Price group: 60

Advantages

- For modular assembly with simple connection segments and intermediate sections 250 and 500 mm high
- Innovative honeycomb structure
- Installation in groundwater up to 3000 mm

Description

The chamber module for wet or dry installation is equipped with fitted access steps in accordance with DIN EN 13101 and BGR 177, all the necessary seals and connecting wedges as well as a taper with vertically adjustable upper section. The intermediate sections made of permanently resistant polymer (PE) have universal connection possibilities. Thanks to the modular KESSEL system, the design can be flexibly combined with intermediate sections, taper, upper section and cover.

General characteristics

Colour: black
Material: PE-HD
Standard: EN 13598-2

Installation situation: underground installation

Delivery state: Partly for on-site assembly (access steps have been

pre-mounted in the factory)

Inlet max. scoring (DN): Z-42.1-527

Dimensions

Net weight:220,98 kgGross weight:259,04 kgGroundwater resistant from lower edge of base3000 mm

section:

Installation depth: 2130 - 2379 mm

Vertical adjustment: vertically adjustable upper section

Length:1200 mmWidth:1200 mmPackaging dimension:lengthPackaging dimension:widthPackaging dimension:height



Tank/drain body

Number of inlets: 150 mm
Clear width of tank (LW): 1000 mm
Clear width of entry (LW): 600 mm

Coverage features

Type of cover: Round cover plate

Cover material:

Colour of cover:

Width of cover:

Height of cover:

Length of cover:

Surface:

Cover locking:

Grey iron

659 mm

Grey iron

Grey iron

locked

Load class: D 400 (EN 124)

Tightness: surface water resistant